

IMERGY ESP30™ SERIES

15-45 kW, 120-200 kWh



Large Scale Energy Storage Platform (ESP)

Imergy Power Systems' versatile energy storage solutions will reduce your energy costs and provide you with better power quality, reliability and resilience. This turnkey energy storage solution is inherently scalable with available powers ranging from kilowatts to multiple megawatts and, independently, with available energy ranging from two to twelve hours output duration. Imergy's solutions integrate seamlessly with intermittent renewable power sources in applications ranging from grid-connected commercial buildings, to islanding smart microgrids, to utility-scale solar and wind, and enable multiple benefits such as demand cost reduction, shifting peak generation to match peak load, and operation regardless of grid failure. Our disruptive patented technology, with long life and unlimited charge-discharge cycle capability, puts the power in your hands.

Key Features

- Turnkey solution in secured weatherproof enclosure
- Safe: non-flammable, non-explosive
- Modular and scalable; ability to independently size power and energy
- Unlimited cycles; partial, full, at any DOD
- 100% performance at all temperatures
- Long life and lowest LCOE of all battery storage systems
- Power security (system can operate in full islanded mode)
- Power quality (fast response time for seamless power source transitions, load transients, PV firming)
- Smart grid ready monitoring and communication
- Low maintenance
- Sustainable design; recyclable, reusable

Key Applications

- Peak shaving
- Demand response
- Energy shifting
- Utility grid ancillary services
- Renewable energy firming
- Microgrid and back-up power

Imergy ESP30™ Specification

Parameter		Rating	Comments
Power rating output (nominal)	380 to 480V 50/60Hz	15-45 kW [50kVa (PF=0.8)]	Excludes pulse capability
Response time AC	-100% to 100% output	<70ms	Excludes communication latency effects
Transition between Grid and islanded modes			
Dimensions	L x W x H	6 x 2.4 x 2.6 m / 20 x 8 x 8.5 ft	20 foot container
Containerized electrolyte		Determined by hours of storage	Includes secondary containment
Cycles		100,000	No limit. Based on life only
DC DC efficiency		70-75%	Measured at constant current over 100% duty cycle
Storage duration		Up to 7 hours at nominal power	A function of electrolyte tank selection
Capacity range (DOD)		0 to 100%	No life impacts
Communications interface		Modbus / TCP/IP	Multiple including CANBUS in multiple strings
Ambient operating conditions		-20°C to +55°C / -4°F to +131°F	Conditioned space not required
Altitude		Up to 2000 m / 6,562 ft	AC derated based on PCS and transformer
Relative humidity		0-95%	
Availability figure		99.16%	Single module
Self discharge	%/day	0.010%	
Noise level dBa 1 meter		<70 dBa	
Weight	kg/lbs	12,925 kg / 28,495 lbs	Excludes electrolyte

The system is designed with intent to comply with the following standards: IEEE1547, UL1741, IEC62103 (EN50178)

Specifications are subject to change without notice

Imergy ESP30™ Containerized Module

