



# SolarEdge Power Optimizer

Module Add-On

P300 / P350 / P405 / P500



POWER OPTIMIZER

## PV power optimization at the module-level

- Up to 25% more energy
- Superior efficiency (99.5%)
- Mitigates all types of modules mismatch-loss, from manufacturing tolerance to partial shading
- Flexible system design for maximum space utilization
- Fast installation with a single bolt
- Next generation maintenance with module level monitoring
- Module-level voltage shutdown for installer and firefighter safety



# SolarEdge Power Optimizer Module Add-On

P300 / P350 / P405 / P500

	P300 (for 60-cell modules)	P350 (for 72-cell modules)	P500 (for 96-cell modules)	P405 (for thin film modules)	
<b>INPUT</b>					
Rated Input DC Power <sup>(1)</sup>	300	350	500	405	W
Absolute Maximum Input Voltage (Voc at lowest temperature)	48	60	80	125	Vdc
MPPT Operating Range	8 - 48	8 - 60	8 - 80	12.5 - 125	Vdc
Maximum Continuous Input Current (Isc)	10				Adc
Maximum Efficiency	99.5				%
Weighted Efficiency	98.8				%
Overvoltage Category	II				
<b>OUTPUT DURING OPERATION (POWER OPTIMIZER CONNECTED TO OPERATING INVERTER)</b>					
Maximum Output Current	15				Adc
Maximum Output Voltage	60		85		Vdc
<b>OUTPUT DURING STANDBY (POWER OPTIMIZER DISCONNECTED FROM INVERTER OR INVERTER OFF)</b>					
Safety Output Voltage per Power Optimizer	1				Vdc
<b>STANDARD COMPLIANCE</b>					
EMC	FCC Part15 Class B, IEC61000-6-2, IEC61000-6-3				
Safety	IEC62109-1 (class II safety), UL1741				
RoHS	Yes				
Fire Safety	VDE-AR-E 2100-712:2013-05				
<b>INSTALLATION SPECIFICATIONS</b>					
Maximum Allowed System Voltage	1000				Vdc
Dimensions (W x L x H)	141 x 212 x 40.5 / 5.55 x 8.34 x 1.59				mm / in
Weight (including cables)	950 / 2.1				gr / lb
Input Connector	MC4 / Amphenol / Tyco / H+S			MC4	
Output Connector	MC4				
Output Wire Length	0.95 / 3.0	0.95 / 3.0 or 1.2 / 3.9	1.2 / 3.9		m / ft
Operating Temperature Range	-40 - +85 / -40 - +185				°C / °F
Protection Rating	IP65 / NEMA4				
Relative Humidity	0 - 100				%

<sup>(1)</sup> Rated STC power of the module. Module of up to +5% power tolerance allowed.

PV SYSTEM DESIGN USING A SOLAREGE INVERTER <sup>(2)</sup>	SINGLE PHASE		THREE PHASE	
	Minimum String Length (Power Optimizers)	8		16
Maximum String Length (Power Optimizers)	25		50	
Maximum Power per String	5250		11250	W
Parallel Strings of Different Lengths or Orientations	Yes			

<sup>(2)</sup> It is not allowed to mix P405 with P300/P350/P500/P600/P700 in one string.

